

Link do produktu: <https://www.multiproject.com.pl/kamera-ip-tubowa-sno-l6013rp-2mpix-3-6mm-p-11689.html>



Kamera IP tubowa SNO-L6013RP 2Mpix 3,6mm

Cena brutto	1 057,82 zł
Cena netto	860,02 zł
Czas wysyłki	24 godziny
Numer katalogowy	12523
Producent	Samsung Techwin

Opis produktu

Cechy produktu

- Rozdzielczość maksymalna obrazu 2MPX (1920x1080)
- Obiektyw zmiennoogniskowy 3.6mm
- Czułość: 0.15Lux F1.8 (Color), 0Lux F1.8 (B/W : IR LED on)
- 30kl./s przy dowolnej rozdzielczości obrazu
- Gniazdo na kartę SD/SDHC, zasilanie PoE
- Zasięg oświetlenia IR: 20m, IP66
- Tryb korytarzowy (obrot obrazu o 90°/270°)
- Tryb LDC (kompensacja zniekształceń obiektywu)

Specyfikacja

Wideo	1/2.9" 2.19M CMOS
Przetwornik	2,000(H) x 1,121(V)
Całkowita liczba pikseli	1,984(H) x 1,105(V)
Efektywna liczba pikseli	Progressive
System skanowania	Color : 0.15Lux (1/30sec, F1.8), 0.003Lux (2sec, F1.8) B/W : 0Lux (IR LED on)
Min. oświetlenie	
Obiektyw	3.6mm stały
Odległość ogniskowa (współczynnik zoomu)	F1.8
Maks. otwór przesłony	H : 86.5° / V : 47.8° / D : 101.2°
Kąt pola widzenia	0.5m (1.64ft)
Min. odległość od obiektu	Fixed
Lens Type	Wbudowany
Typ mocowania	
Parametry funkcjonalne	20m
Odległość obserwacji	Wyl./wl. (wyświetlanie do 15 znaków)
Nazwa kamery	Tak
Dzień/noc	wyl. / BLC
Kompensacja tylnego oświetlenia	SSDR (ang. Samsung Super Dynamic Range – super zakres dynamiki Samsung)
Poprawa kontrastu	(wyl./wl.)
	SSNR (wyl. / wl.)
Cyfrowa redukcja szumów	Wyl./wl. (4 programowalne strefy)
Detekcja ruchu	Off / On (6ea rectangular zones)
Strefy prywatności	Off / Low / Middle / High
Gain Control	ATW / AWC / Manual / Indoor / Outdoor
Balans bieli	Off / On (5 levels with min / max)
LDC (Lens Distortion Correction)	Minimum / Maximum / Anti flicker
Electronic Shutter Speed	Flip / Mirror / Hallway view
Flip / Mirror	Motion detection with metadata, Tampering
Intelligent Video Analytics	Motion detection, Tampering detection, SD card error, NAS error
Alarm Triggers	File upload via FTP and E-mail, Local storage recording at event, Notification via E-mail
Alarm Events	
Sieć	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, MJPEG
Resolution	1920 x 1080, 1280 x 960, 1280 x 720, 1024 x 768, 800 x 600, 720 x 576, 640 x 480, 320 x 240
Max. Framerate	H.264 : Max. 30fps at all resolutions MJPEG : Max. 1fps at 1920 x 1080, 1280 x



Video Quality Adjustment	960, 1280 x 720, 1024 x 768, Max. 15fps at other resolution
Bitrate Control Method	H.264 : Target bitrate level control, MJPEG : Quality level control
Streaming Capability	H.264 : CBR or VBR, MJPEG : VBR
Audio I/O	Multiple streaming (Up to 3 profiles)
Audio Compression Format	Line in G.711 u-law / G.726 selectable G.726 (ADPCM) 8KHz, G.711 8KHz, G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
Audio Communication	Uni-directional audio
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour HTTPS(SSL) login authentication, Digest login authentication IP address filtering, User access log, 802.1x authentication
Security	Unicast / Multicast 6 users at unicast mode micro SD/SDHC max. 32G, NAS - Motion images recorded in the SD memory card can be downloaded - Manual recording at local PC
Streaming Method	ONVIF Profile S, G, SUNAPI (HTTP API)
Max. User Access	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek, Norwegian, Finnish
Storage	Supported OS : Windows XP / VISTA / 7 / 8 / 8.1, MAC OS X 10.7 ~ 10.10 Supported Browser : Microsoft Internet Explorer (Ver. 8 ~ 11), Mozilla Firefox (Ver. 9 ~ 35), Google Chrome (Ver. 15 ~ 40), Apple Safari (Ver. 8.0.2(Mac OS X 10.10), 7.0.6(Mac OS X 10.9), 6.0.2 (Mac OS X 10.8, 10.7 only), 5.1.7) * Mac OS X only
Application Programming Interface	SmartViewer
Webpage Language	-30°C ~ +55°C (-22°F ~ +131°F) / Less than 90% RH *Start up should be done at above -20°C (-4°F) -30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Web Viewer	IP66
Central Management Software	PoE (IEEE802.3af, Class2)
Environmental	Max. 5.7W
Operating Temperature / Humidity	Dark gray / Plastic
Storage Temperature / Humidity	O58.6 x 165.2mm (O2.31" x 6.5") (Without sunshield)
Ingress Protection	250g
Electrical	
Input Voltage / Current	
Power Consumption	
Mechanical	
Color / Material	
Dimensions (WxH)	
Weight	